



## Industrial-Grade Worksite Matting and Rig Mats

<b>Module Size</b>	<p><b>Large Mat</b> Actual: 7.5' (L) x 14' (W) x 4" thickness (105 sq/ft) 2.286m x 4.267m x 10.16cm (9.75 sq/m)</p> <p>Useable (due to flange): 6.5' (L) x 13' (W) x 4" thickness (84.5 sq/ft) 1.981m x 3.962m x 10.16cm (7.85 sq/m)</p> <p><b>Small Mat</b> Actual: 7.5' (L) x 7.5' (W) x 4" thickness (56.25 sq/ft) 2.286m x 2.286m x 10.16cm (5.23 sq/m)</p> <p>Useable (due to flange): 6.5' (L) x 6.5' (W) x 4" thickness (42.25 sq/ft) 1.981m x 1.981m x 10.16cm (3.93 sq/m)</p>
<b>Flange Thickness</b>	2" (5.08cm)
<b>Weight</b>	<p>Large: 1,150 lbs / 521.63 kg</p> <p>Small: 525 lbs / 238.14 kg</p>
<b>Color</b>	Beige. Custom colors available.
<b>Material</b>	High-Density Polyethylene (HDPE) with special impact modifiers and fillers to accommodate thermal expansion, incorporate UV resistance, add anti-static properties.

<b>Weight Loading</b>	600 psi
<b>Flammability Resistance</b>	UL94HB
<b>Ground Surface</b>	Designed to be used with no ground preparation over grass, mud, sand, dirt, and other common on-site substances.
<b>Connection System</b>	Proprietary, self-aligning, aluminum cam lock system. Connects the overlapping flange from adjacent mats with a simple twist of a standard hex key.
<b>Construction Features</b>	<ul style="list-style-type: none"> <li>• Sealed design prevents fluid saturation of mat</li> <li>• Enhanced traction</li> <li>• Dual-sided</li> </ul>
<b>Shipping Info</b>	<p>U.S. Standard Truck: 40 mats – 3 stacks each; 12, 14, and 14 mats high</p> <p>40ft ISO shipping container: 40 mats – 2 stacks of 20 mats high, 3 stacks of 12, 14, and 14 mats high</p> <p>20ft ISO shipping container: 20 mats – 1 stack, 20 full mats high</p>

